

Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924
International Emergency: 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 03325 REARVIEW MIRROR ADHESIVE KIT PART 1
Item No: PTXSA6128B
Product Type: Adhesive

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:
POLYURETHANE METHACRYLATE RESIN MIXTURE	40-50	Not Listed	Not Listed
(METH)ACRYLATE MONOMER MIXTURE	40-50	Not Listed	Not Listed
ACRYLIC ACID 79-10-7	1-10	2 ppm TWA	10 ppm TWA; 30 mg/m ³ TWA
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<3	Not Listed	Not Listed
SACCHARIN 81-07-2	0.1-1.0	10mg/m ³ nuisance dust	Not Listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Repeated skin contact may cause allergic skin reactions. May cause pain, redness or swelling of the eyes and excessive blinking and tear production.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
ACRYLIC ACID 79-10-7	1-10		A4 - Not Classifiable as a Human Carcinogen	Group 3 Monograph 71, 1999; Supplement 7, 1987; Monograph 19, 1979
SACCHARIN 81-07-2	0.1-1.0	Delisted April 2000		Group 3: Vol 73, Page 517: 1999

Medical Conditions Recognized as Being Aggravated by Exposure: Acrylic acid: Upper respiratory and lung diseases, dermatitis.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Move to fresh air in case of accidental inhalation of vapours.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): >200° F
Recommended Extinguishing Media: Carbon dioxide, dry chemical, foam
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus.
Hazardous Products of Combustion: Irritating vapors
Unusual Fire/Explosion Hazards: None.

Lower Explosive Limit: 2.0% Acrylic acid
Upper Explosive Limit: 8.0% Acrylic acid

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store below 100 degrees F.
Handling: Do not inhale vapors. Avoid prolonged skin contact. Keep away from eyes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Rubber or plastic gloves.
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Yellow liquid
Odor: Irritating
Boiling Point: >300°F
pH: Does not apply
Solubility in Water: Slight
Specific Gravity: 1.1 @ °C
VOC Content(Wt.%): 30% by weight
Vapor Pressure: Not determined
Vapor Density (Air=1): Not Determined
Evaporation Rate: Not Determined

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: WILL NOT OCCUR.
Incompatibilities: Avoid contact with bases and strong oxidizers
Conditions to Avoid: Heat
Hazardous Products of Combustion: Irritating vapors

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Unrestricted
Hazard Class: None
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Not regulated
Class or Division: None
UN/NA Number: None

IMDG

Product Name: 03325 REARVIEW MIRROR ADHESIVE
KIT PART 1

Item No: PTXSA6128B

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

ACRYLIC ACID, DIMETHYLBENZYL HYDROPEROXIDE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 1

Estimated HMIS Classification: HEALTH 2, FLAMMABILTY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Health and Safety Manager
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: December/20/2006

Revision Number: 2

Telephone No.: 1-87-Permatex (877) 376-2839

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924
 International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 03325 REARVIEW MIRROR ADHESIVE KIT PART 2
Item No: PTXAS752C
Product Type: Activator

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
HEPTANE 142-82-5	>60	400 ppm	500 ppm; 2000 mg/m ³
PROPANE 74-98-6	5-15	1000 ppm	1000 ppm; 1800 mg/m ³
ISOBUTANE 75-28-5	5-15	1000 ppm	Not listed
ETHANOL 64-17-5	<2	1000 ppm	1000 ppm; 1900 mg/m ³
ORGANO-COPPER COMPOUND 68084-48-0	<1	Not listed	Not listed
ORGANO-COPPER COMPOUND 22221-10-9	<1	Not listed	Not listed
ORGANO-COPPER COMPOUND 85737-14-0	<1	Not listed	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. Ingestion may irritate digestive tract and cause nausea, vomiting and diarrhea. Aspiration hazard if swallowed. Excessive inhalation causes headache, dizziness, nausea, and incoordination.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Contact with eyes may cause tearing and redness. Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. May cause skin irritation.

Component	Weight%	NTP	ACGIH Carcinogens	IARC
ETHANOL 64-17-5	<2		A4 - Not Classifiable as a Human Carcinogen	

Medical Conditions Recognized as Being Aggravated by Exposure: May aggravate preexisting dermatitis. Since this product contain copper compounds, individuals with Wilson's Disease should avoid exposure to this product.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): Extremely flammable aerosol per flame extension test
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers.
Hazardous Products of Combustion: Oxides of carbon, Copper oxide, Phosphorus acids

5. FIRE FIGHTING MEASURES

Unusual Fire/Explosion Hazards:

Vapors may travel from container toward sources of ignition and flashback. Contents under pressure. Closed containers may rupture or explode when exposed to extreme heat. Keep containers cool. Do not puncture or incinerate container.

Lower Explosive Limit:

1.0

Upper Explosive Limit:

9.5

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).

Handling:

Avoid contact with skin and eyes. Do not inhale vapors. Keep away from heat and open flame. Do not puncture or incinerate container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses.

Skin:

Neoprene or nitrile gloves recommended.

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection:

An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Green liquid

Odor:

Solvent

Boiling Point:

Not determined

pH:

Does not apply

Solubility in Water:

Negligible

Specific Gravity:

0.66

VOC(Wt.%):

97.6% by weight

Vapor Pressure:

71psig @ 70°F

Vapor Density (Air=1):

>1

Evaporation Rate:

<1 (ethyl ether = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

Will not occur.

Incompatibilities:

Avoid contact with bases and strong oxidizers, Acids

Conditions to Avoid:

Keep away from heat, sparks and open flame. - No smoking.

Hazardous Products of Combustion:

Oxides of carbon, Copper oxide, Phosphorus acids

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:

Disposal should be made in accordance with federal, state and local regulations.. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

US EPA Waste Number:

D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Product Name: 03325 REARVIEW MIRROR ADHESIVE
KIT PART 2

Item No: PTXAS752C

14. TRANSPORTATION INFORMATION

Ground Transport (DOT)

DOT Shipping Name: Consumer Commodity (not more than one liter)
Hazard Class: ORM-D
UN/ID Number: None

IATA

Proper Shipping Name: Consumer Commodity (Not more than 1 liter)
Class or Division: Class 9
UN/ID Number: ID 8000

IMDG

Proper Shipping: Aerosols, Limited Quantity
Hazard Class: Class 2.1
UN Number: UN 1950

Marine Pollutant: Copper

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

COPPER COMPOUND

California Proposition 65: No California Prop 65 chemicals are known to be present.

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 4, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 4, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: June 17, 2009

Revision 2

Number:

Telephone No.: 1-87-Permatex (877) 376-2839