Page 1 of 5 Thursday, March 06, 2008

# MSDS - Material Safety Data Sheet Product Name: WIRE DRYER (UPC: 078698131313)

MSDS No.: M1306

# I. Basic Information:

Manufacturer: RADIATOR SPECIALTY COMPANY

Address: 600 RADIATOR ROAD

City, ST Zip: INDIAN TRAIL, NC 28079

Country:

Contact: Robert Geer

Information Telephone Number: 704-684-1811

Emergency Contact: Rocky Mountain Poision Control Center

**Emergency Telephone Number: 303-623-5716** 

**Emergency Restrictions:** 

Product Name: WIRE DRYER (UPC: 078698131313)

MSDS No.: M1306

**Issue Date:** 03/06/2008 **Supersedes Date:** 11/19/2003

# II. Hazards Identification:

## **EMERGENCY OVERVIEW**

Danger: Flammable. Harmful or fatal if swallowed. Eye and skin irritant. Contents under pressure.

Level 3 Aerosol

#### **OSHA Regulatory Status**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

#### **Potential Health Effects**

#### Route(s) of Entry:

Absorption, Inhalation, and Ingestion.

#### Health Hazards (Acute and Chronic):

See signs and symptoms below

## Signs and Symptoms:

Eye Contact: Irritant. Prolonged contact may cause conjunctivitis. Skin Contact: Irritant. Defatting of tissue, dermatitis may occur.

Inhalation: Irritant to mucous membranes. Repeated exposure may cause narcosis, dizziness, respiratory or lung irritation.

Ingestion: HARMFUL OR FATAL IF SWALLOWED. May cause burns to mouth, throat & stomach.

## Medical Conditions Generally Aggravated by Exposure:

None Known

## Other Health Warnings:

Vomiting and subsequent aspiration into the lungs may lead to chemical pneumonia and pulmonary edema which is a potentially fatal condition.

## Potential Environmental Effects

Not Available

# III. Composition/Information on Ingredients:

Chemical Name	CAS No.	% Range	Trade Secret
1,2,4-Trimethylbenzene	95-63-6	1.0 - 5.0	
2-Butoxy-1-Ethanol	111-76-2	1.0 - 5.0	
Aliphatic Hydrocarbon - Non Exempt.	8052-41-3	30.0 - 60.0	
Carbon dioxide	124-38-9	1.0 - 5.0	
Mesitylene	108-67-8	1.0 - 5.0	
Naphthenic Petroleum Distillate	64742-52-5	30.0 - 60.0	
Xylene (mixed isomers)	1330-20-7	1.0 - 5.0	

Page 2 of 5 Thursday, March 06, 2008

# MSDS - Material Safety Data Sheet Product Name: WIRE DRYER (UPC: 078698131313)

MSDS No.: M1306

## IV. First Aid Measures:

# **Emergency and First Aid Procedures:**

Eye Contact: Flush eyes with clean water for 20 minutes while lifting eyelids. Get prompt medical attention.

Skin Contact: Wash skin with soap and water thoroughly. If adverse effects persist, get prompt medical attention. Remove and isolate contaminated clothing. Launder contaminated clothing before reuse.

Inhalation: Move victim to fresh air. If breathing becomes difficult, administer oxygen and get prompt medical attention. If breathing stops, give artificial respiration and get prompt medical attention.

Ingestion: DO NOT INDUCE VOMITING! Call Poison Control Center, physician, or hospital emergency room immediately. Aspiration of vomitus into the lungs can cause pneumonitis, which can be fatal.

#### Note to Physicians:

N/F

# V. Fire Fighting Measures:

#### Suitable Extinguishing Media:

Water Fog, Foam, Carbon Dioxide, Dry Chemical

#### **Unsuitable Extinguishing Media:**

Do not use forced water stream as this could cause the fire to spread.

#### **Products of Combustion:**

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

#### Protection of Firefighters:

Wear self-contained positive pressure breathing apparatus and protective clothes. Use shield to protect from rupturing and venting containers. At elevated temperatures containers may vent, rupture or burst, even violently

## VI. Accidental Release Measures:

#### **Personal Precautions:**

Eliminate all ignition sources. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

#### Environmental Precautions:

Prevent run-off to sewers, streams, or other bodies of water. If run-off occurs, notify proper authorities as required that a spill has occured. Run off to sewer may create fire or explosion hazard.

### **Methods for Containment:**

Dike or contain spill and absorb with inert materials (sand, sawdust, absorbent sweeping compounds, rags, etc).

#### Methods for Cleanup:

Using a non-metalic scoop, place contaminated material into an approved chemical waste container. Where possible, vacuum spilled liquid using an explosion proof vacuum to recover material.

## Other Information:

All equipment used with handling the concentrate must be grounded. If run-off occurs, notify proper authorities as required that a spill has occured.

## VII. Handling and Storage:

#### **Handling Precautions:**

Use with adequate ventilation and proper protective equipment.

Do not use or store near fire, sparks, or open flame. Do not puncture or incinerate container. Exposure to temperatures above 120° may cause container to vent, rupture, or burst.

### **Storage Precautions:**

Store in cool, well ventilated area below 120°F away from heat, fire, sparks or flame.

## VIII. Exposure Controls/Personal Protection:

Page 3 of 5 Thursday, March 06, 2008

# MSDS - Material Safety Data Sheet Product Name: WIRE DRYER (UPC: 078698131313)

MSDS No.: M1306

Chemical Name	OSHA PEL	ACGIH TLV	Other Limits
Aliphatic Hydrocarbon - Non Exempt.	100 ppm	100 ppm	Not Available
2-Butoxy-1-Ethanol	50 ppm	25 ppm	Not Available
Carbon dioxide	N/AV	5000 ppm	Not Available
1,2,4-Trimethylbenzene	N/E	25 ppm	Not Available
Naphthenic Petroleum Distillate	5 mg/m3	5 mg/m3	Not Available
Mesitylene	N/A	N/A	Not Available
Xylene (mixed isomers)	100 ppm	100 ppm	Not Available

#### **Engineering Controls:**

Use with adequate ventilation. If TLV is exceeded, wear NIOSH approved respirator.

#### **Personal Protective Equipment:**

See Section 2 for applicable exposure limits. For prolonged exposure wear protective safety glasses, gloves, and apron.

# IX. Physical and Chemical Properties:

**Boiling Point**: 320 F **Boiling Range**: N/D

Solubility In Water: Insoluble

Flash Point: 132F

Odor Threshold: N/D

Vapor Density (AIR = 1): N/D

pH Range: N/A

Decomposition Temp: N/D Lower Explosive Limit: 0.7% Specific Gravity (H20 = 1): 0.81

Other Information: VOC Content: 44.0 %

Melting Point: N/A Freezing Point: N/D

Evaporation Rate (Butyl Acetate = 1): N/A

Flash Point Method: TCC

Appearance and Odor: Clear light yellow with sweet vanilla odor

Vapor Pressure (mm Hg.): N/D
Partition Coefficient: N/D
Auto-Ignition Temp: N/D
Upper Explosive Limit: 5%

# X. Stability and Reactivity:

## Stability:

Product is stable

## **Conditions to Avoid:**

Avoid heat, sparks, and flames. Avoid incompatible materials.

# Incompatible Materials:

Avoid contact with strong oxidizers

## **Hazardous Decomposition Products:**

Normal products of combustion, smoke, carbon dioxide, carbon monoxide, and sulfur trioxides.

### Possibility of Hazardous Reactions:

Will not occur

# XI. Toxicological Information:

N/D

Page 4 of 5 Thursday, March 06, 2008

# MSDS - Material Safety Data Sheet Product Name: WIRE DRYER (UPC: 078698131313)

MSDS No.: M1306

# XII. Ecological Information:

N/D

# XIII. Disposal Considerations:

DISPOSAL: This container may be recycled in aerosol recycling centers when empty. Before offering for recycling, empty the can by using the product according to the label. DO NOT PUNCTURE! If recycling is not available, wrap the container and discard in the trash. Dispose of unused product in accordance with all local, state government and federal laws and regulations.

## XIV. Transport Information:

Shipping Name: Consumer Commodity

DOT Hazard Class: ORM-D DOT Subsidiary Hazard Class: Not Available

UN/NA#: 1950 Packing Group: Not Available

**Transportation Information:** DOT Hazard Class: ORM-D

Shipping Name: Consumer Commodity

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for international and air shipping purposes.

ICAO/IATA (US)

Shipping Name: Aerosols

Class: 2.1

UN number: UN1950

International:

ICAO/IATA

UN number: UN1950 Shipping Name: Aerosols

Class: 2.1

**IMDG** 

UN number: UN1950 Shipping Name: Aerosols

Class: 2.1 EmS: F-D, S-U

## XV. Regulatory Information:

See Section 2 for SARA Reportable Chemicals.

USA TSCA: All components of this material are either exempt or listed on the US TSCA Inventory.

Warning: This product contains a chemical(s) known to the State of California to cause cancer or birth defects or other reproductive harm.

New Jersey RTK

Aliphatic Hydrocarbon 8052-41-3 1,2,4-Trimethylbenzene 95-63-6 1,3,5-Trimethylbenzene 108-67-8 **Xylene** 1330-20-7

Pennsylvania RTK

Aliphatic Hydrocarbon 8052-41-3 1,2,4-Trimethylbenzene 95-63-6 Xylene 1330-20-7

# MSDS - Material Safety Data Sheet Product Name: WIRE DRYER (UPC: 078698131313)

MSDS No.: M1306

XVI. Other Inform	ation:					
Chemical State:	X Liquid	Gas	Solid	NFPA	Fire	
Chemical Type:	Pure	<b>X</b> Mixture	<u> </u>	Health	2 Reastivity	
Hazard Category:				2	0	
<b>X</b> Acute	Chronic Pressure	X Fire Reactive			Special	
Additional Manufacture	er Warnings:				Ť	
Do not used in confined area without proper ventilation. Contact lenses may cause further damage in case of splash into eye. KEEP AWAY FROM			2	Health		
CHILDREN AND ANIMALS!		2	Flammability			
N/E: Not Established				0	Physical Hazard	
N/D: Not Determined N/A: Not Applicable				С	Pers. Protection	

#### **Additional Product Information:**

N/AV: Not Available

While Radiator Specialty Company believes this data is accurate as of the revision date, we make no warranty with respect to the data and we expressly disclaim all liability for reliance thereon. The data is offered solely for information, investigation, and verification. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.