

Permatex, Inc.
 10 Columbus Blvd.
 Hartford, CT 06106
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 1C FORM-A-GASKET #1 SEALANT 11OZ
Item No: 80003
Product Type: Sealant

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
KAOLIN 1332-58-7	50-60	2 mg/m ³ dust	10 mg/m ³ dust; 5 mg/m ³ respir.
ROSIN 8050-09-7	20-30	sensitizer; reduce exposure to as low as possible	15 mg/m ³ total dust; 5 mg/m ³ respir.
2-PROPANOL 67-63-0	10-20	400 ppm TWA; 983 mg/m ³ TWA	400 ppm TWA
VEGETABLE OIL 68187-84-8	1-10		
TITANIUM DIOXIDE 13463-67-7	1-10	10 mg/m ³	10 mg/m ³ ; 15 mg/m ³ total dust
SILICA, QUARTZ 14808-60-7	1-5	0.05 mg/m ³ TWA respirable	0.1 mg/m ³ TWA respirable

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye, skin and respiratory irritation. Oral LD50 greater than 5000 mg/kg. This product contains encapsulated silicon dioxide (quartz silica). No exposure to free respirable silica is anticipated during normal use of this product. Silica may be released by grinding or machining of coated material. Use NIOSH-approved dust/mist respirator when grinding or machining.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation.

Signs and Symptoms of Exposure: Excessive accidental exposure may cause headache, dizziness, nausea and mild respiratory irritation. Overexposure may cause eye and skin redness.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
TITANIUM DIOXIDE 13463-67-7	1-10			Group 3; Vol 47, pg 307, 1989
SILICA, QUARTZ 14808-60-7	1-5	Known Carcinogen		Group 1; Vol. 68; 1997

Medical Conditions Recognized as Being Aggravated by Exposure: Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.

Inhalation: If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin Contact: Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

Product Name: 1C FORM-A-GASKET #1 SEALANT 11OZ
Item No: 80003

5. FIRE FIGHTING MEASURES

Flash Point (°F/C): Does not apply. Per ASTM D4359 this product is a solid.
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.
Hazardous Products Formed by Fire or Thermal Decomposition: Aldehydes, Oxides of carbon. Carboxylic acids
Unusual Fire/Explosion Hazards: Closed containers may rupture or explode when exposed to extreme heat.
Lower Explosive Limit: 2
Upper Explosive Limit: 12

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Residues may be cleaned up with isopropyl alcohol.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.
Handling: Avoid contact with skin and eyes. Do not inhale vapors. Keep container closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses or goggles.
Skin: Rubber or plastic gloves
Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits during the use of this product.
Respiratory Protection: An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Reddish brown paste
Odor: Alcohol Odor
Boiling Point (°F): 180 degrees F.
pH: Does not apply
Solubility in Water: Partial
Specific Gravity: 1.5
VOC Content(Wt.%): 15.4 % by weight; 231 g/l
Vapor Pressure: 33 mm Hg @ 68 degrees F.
Vapor Density (Air=1): 2.07
Evaporation Rate: 7.7 (ether = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: WILL NOT OCCUR
Incompatibilities: Strong oxidizers.
Conditions to Avoid: Do not expose to heat or store at temperatures above 120 F.
Hazardous Products Formed by Fire or Thermal Decomposition: Aldehydes, Oxides of carbon. Carboxylic acids

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

Product Name: 1C FORM-A-GASKET #1 SEALANT 11OZ
Item No: 80003

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Domestic Ground Transport

DOT Shipping Name: Unrestricted
Hazard Class: NONE
UN/ID Number: None
Marine Pollutant: None

IATA

Proper Shipping Name: Unrestricted
Class or Division: None
UN/NA Number: None

IMDG

Proper Shipping: Unrestricted
Hazard Class: None
UN Number: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.
NONE

CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status:

All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 0
Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.
HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd Health and Safety Manager
Company: Permatex. Inc. 10 Columbus Blvd. Hartford, CT 06106
Telephone Number: 1-87-Permatex (877) 376-2839
Revision Date: 06/20/2001

Revision Number: 2